ROLLY 71/2 E 33



COMPACT WALK BEHIND SCRUBBER DRYERS ROLLY SERIES

The new ultra-compact scrubber dryer Rolly 7 ½ is the right answer to the professional cleaning demand. Comfort in narrow spaces, where no one arrives: - 7,5 liters of tank capacity, its dimensions, combined with a special handle (patented) and swivel wheels allow Rolly to go and work in small areas. Top cleaning and drying results: - the cylindrical brush deck, with three different down pressure adjustable by knob, against every kind of dirt; - an unbelievable alternate twin squeegee system (patented), for top drying results and optimized consumptions at the same time; - low noise level (only 54 dbA), perfect for day cleaning and in all the environments (hospitals, resthomes, schools...) where silence is a must. A start & go machine No training required, everybody can use Rolly: - all the main functions can be managed by the intuitive control panel; - coloured levers and knobs clearly help the user preparing the machine for work or while using it; - effortless maintenance. Rolly ½ E 33 is the electric version with a standard power supply kit case and a 15 meters cable.





with unlockling system



Ergonomic handle Adjustable down pressure by knob . (3 steps)



Power supply kit case



Alternate twin squeegee system (patented)



Compact dimensions to go and work where no one arrives



Fast and easy maintenance



Easy to trasport, park, store

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROLLY 7½ E 33	10.1075.01	1

ΤΕCΗΝΙCΑΙ ΠΑΤΑ

I LUIINIUAL DAIA		
FEATURES		
Cleaning width	mm	330
Squeegee width	mm	420
Productivity (theor./practical)	m²/h	1320 - 800
Power supply		Cable 230 V - 50 Hz
Installed power	W	270
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	80 - Cyl. x 1
Motor rating x No	Wxnr	120 x 1
Motor speed	rpm	800
Contact pressure	g /cm²	35 - 71 - 160
TRACTION		
Motor rating	W	

STANDARD	ACCESSORIES

ТҮРЕ	REF. NO.
Polypropylene cylindrical blue brush	40.5000.00
Set front/rear polyurethane squeegee blade	96.0084.00
Set front/rear rubber squeegee blade	96.0085.00
Kit case power supply 230V	22.0509.00

^(*) Silent mode function

Driving speed	Km/h	4
Hill climbing ability	%	2
VACUUM		
Motor rating	W	150
Vacuum	mbar/mmH20	48/490
Airflow rating	I/s	30
Noise level	dB(A)	58 / 54 *
TANK		
Туре		Double tank
Cleaning solution tank	I	7,5
Recovery tank	I	8
Weight (empty/with batteries)	Kg	23/25,5
Power supply cable	m	15
Dimensions	mm	640x450x422

OF HUNAL AUGESSUNIES	
ТҮРЕ	REF. NO.
Soft cylindrical polypropylene brush	40.5000.01
Hard cylindrical polypropylene brush	40.5000.02
Tynex cylindrical brush grit 360	40.5000.03
Tynex cylindrical brush grit 80	40.5000.08
Microfiber cylindrical brush	40.5000.04
Case batteries Li Fe PO4 24V 10 Ah	22.0508.00
Case batteries Li Fe PO4 24V 20 Ah	22.0508.01
24V 5A charger	18.0056.00
Car charger 24-12V 3A	18.0065.00

ROLLY 71/2 M 33

PATENTED

COMPACT WALK BEHIND SCRUBBER DRYERS ROLLY SERIES

The new ultra-compact scrubber dryer Rolly 7 ½ is the right answer to the professional cleaning demand. Comfort in narrow spaces, where no one arrives: - 7,5 liters of tank capacity, its dimensions, combined with a special handle (patented) and swivel wheels allow Rolly to go and work in small areas. Lithium batteries: a big power in a small case - The last generation lithium batteries hosted in a practical small case guarantees reliability and running time (more than one hour running time with the 10 Ah batteries and more than two hours thanks to the 20 Ah ones). Top cleaning and drying results: the cylindrical brush deck, with three different down pressure adjustable by knob, against every kind of dirt; - an unbelievable alternate twin squeegee system (patented), for top drying results and optimized consumptions at the same time; - low noise level (only 54 dbA), perfect for day cleaning and in all the environments (hospitals, resthomes, schools...) where silence is a must. A start & go machine No training required, everybody can use Rolly: - all the main functions can be managed by the intuitive control panel; - coloured levers and knobs clearly help the user preparing the machine for work or while using it; - effortless maintenance. Rolly 7 ½ M 33 is available with two different batteries variants (10 Ah, 20 Ah) as standard.





Ergonomic handle with unlockling system



Adjustable down pressure by knob (3 steps)



Two types of lithium batteries available (10 Ah and 20 Ah)



Alternate twin squeegee system (patented)



Compact dimensions to go and work where no one arrives



Fast and easy maintenance



Easy to trasport, park, store

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROLLY 7½ M 33 BC 10 Ah	13.0075.01	1
ROLLY 7½ M 33 BC 20 Ah	17.0075.01	1

TECHNICAL DATA

I LUIINIUAL DAIA		
FEATURES		
Cleaning width	mm	330
Squeegee width	mm	420
Productivity (theor./practical)	m²/h	1320 - 800
Power supply		Battery 24 V
Installed power	W	270
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	80 - Cyl. x 1
Motor rating x No	W x nr	120 x 1
Motor speed	rpm	800
Contact pressure	g /cm²	35 - 71 - 160
TRACTION		
Motor rating	W	

STANDARD ACCESSORIES

ТҮРЕ	REF. NO.
Polypropylene cylindrical blue brush	40.5000.00
Set front/rear polyurethane squeegee blade	96.0084.00
Set front/rear rubber squeegee blade	96.0085.00
Case batteries Li Fe PO4 24V 10 Ah (**)	22.0508.00
Case batteries Li Fe PO4 24V 20 Ah (***)	22.0508.01
24V 5A charger	18.0056.00

Driving speed	Km/h	4
Hill climbing ability	%	2
VACUUM		
Motor rating	W	150
Vacuum	mbar/mmH20	48/490
Airflow rating	I/s	30
Noise level	dB(A)	58 / 54 *
TANK		
Туре		Double tank
Cleaning solution tank	1	7,5
Recovery tank	I	8
Weight (empty/with batteries)	Kg	23/26,5
Power supply cable	m	
Dimensions	mm	640x450x422

O	
TYPE	REF. NO.
Soft cylindrical polypropylene brush	40.5000.01
Hard cylindrical polypropylene brush	40.5000.02
Tynex cylindrical brush grit 360	40.5000.03
Tynex cylindrical brush grit 80	40.5000.08
Microfiber cylindrical brush	40.5000.04
Car charger 24-12V 3A	18.0065.00
Kit case power supply 230V	22.0509.00

^(*) Silent mode function

^(**) For 10 Ah version

^(***) For 20 Ah version

ROLLY 11 E 33



COMPACT WALK BEHIND SCRUBBER DRYERS ROLLY SERIES

The new ultra-compact scrubber dryer Rolly 11 is the right answer to the professional cleaning demand. Comfort in narrow spaces, where no one arrives: - 11 liters of tank capacity, its dimensions, combined with a special handle (patented) and swivel wheels allow Rolly to go and work in small areas. Top cleaning and drying results: - the cylindrical brush deck, with three different down pressure adjustable by knob, against every kind of dirt; - an unbelievable alternate twin squeegee system (patented), for top drying results and optimized consumptions at the same time; - low noise level (only 54 dbA), perfect for day cleaning and in all the environments (hospitals, resthomes, schools...) where silence is a must. A start & go machine No training required, everybody can use Rolly: - all the main functions can be managed by the intuitive control panel; - coloured levers and knobs clearly help the user preparing the machine for work or while using it; - effortless maintenance. Rolly 11 E 33 is the electric version, with a standard power supply kit case and a 15 meters cable.









Adjustable down pressure by knob (3 steps)



Power supply kit case



Alternate twin squeegee system (patented)



Compact dimensions to go and work where no one arrives



Fast and easy maintenance



Easy to trasport, park, store

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROLLY 11 E 33	10.1110.01	1

TECHNICAL DATA

I EUTHIONE DATA		
FEATURES		
Cleaning width	mm	330
Squeegee width	mm	420
Productivity (theor./practical)	m²/h	1320 - 800
Power supply		Cable 230 V - 50 Hz
Installed power	W	270
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	80 - Cyl. x 1
Motor rating x No	Wxnr	120 x 1
Motor speed	rpm	800
Contact pressure	g /cm²	35 - 71 - 160
TRACTION		
Motor rating	W	

STANDARD ACCESSORIES

•	
ТҮРЕ	REF. NO.
Polypropylene cylindrical blue brush	40.5000.00
Set front/rear polyurethane squeegee blade	96.0084.00
Set front/rear rubber squeegee blade	96.0085.00
Kit case power supply 230V	22.0509.00

(*) Silent mode function

Km/h	4
%	2
W	150
mbar/mmH20	48/490
I/s	30
dB(A)	58 / 54 *
	Double tank
1	11
I	12
Kg	24/26,5
m	15
mm	640x450x502
	% W mbar/mmH20 I/s dB(A) I I Kg m

OF FIGURAL AUGESSOFIES	
TYPE	REF. NO.
Soft cylindrical polypropylene brush	40.5000.01
Hard cylindrical polypropylene brush	40.5000.02
Tynex cylindrical brush grit 360	40.5000.03
Tynex cylindrical brush grit 80	40.5000.08
Microfiber cylindrical brush	40.5000.04
Case batteries Li Fe PO4 24V 10 Ah	22.0508.00
Case batteries Li Fe PO4 24V 20 Ah	22.0508.01
24V 5A charger	18.0056.00
Car charger 24-12V 3A	18.0065.00

ROLLY 11 M 33




COMPACT WALK BEHIND SCRUBBER DRYERS ROLLY SERIES

The new ultra-compact scrubber dryer Rolly 11 is the right answer to the professional cleaning demand. Comfort in narrow spaces, where no one arrives: - 11 liters of tank capacity, its dimensions, combined with a special handle (patented) and swivel wheels allow Rolly to go and work in small areas. Lithium batteries: a big power in a small case - The last generation lithium batteries hosted in a practical small case guarantees reliability and running time (more than one hour running time with the 10 Ah batteries and more than two hours thanks to 20 Ah ones) Top cleaning and drying results: - the cylindrical brush deck, with three different down pressure adjustable by knob, against every kind of dirt; - an unbelievable alternate twin squeegee system (patented), for top drying results and optimized consumptions at the same time; - low noise level (only 54 dbA), perfect for day cleaning and in all the environments (hospitals, resthomes, schools...) where silence is a must. A start & go machine No training required everybody can use Rolly: - all the main functions can be managed by the intuitive control panel; - coloured levers and knobs clearly help the user preparing the machine for work or while using it; - effortless maintenance. Rolly 11 M 33 is available with two different batteries variants (10 Ah, 20 Ah) as standard.









pressure by knob (3 steps)



Two types of lithium batteries available (10 Ah and 20 Ah)



Alternate twin squeegee system (patented)



Compact dimensions to go and work where no one arrives



Fast and easy

maintenance

Easy to trasport. park, store



PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
ROLLY 11 M 33 BC 10 Ah	13.0110.01	1
ROLLY 11 M 33 BC 20 Ah	17.0110.01	1

TECHNICAL DATA

FEATURES		
Cleaning width	mm	330
Squeegee width	mm	420
Productivity (theor./practical)	m²/h	1320 - 800
Power supply		Battery 24 V
Installed power	W	270
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	80 - Cyl. x 1
Motor rating x No	W x nr	120 x 1
Motor speed	rpm	800
Contact pressure	g /cm²	35 - 71 - 160
TRACTION		
Motor rating	W	

STANDARD ACCESSORIES

OTATION TO ACCESSION TO	
TYPE	REF. NO.
Polypropylene cylindrical blue brush	40.5000.00
Set front/rear polyurethane squeegee blade	96.0084.00
Set front/rear rubber squeegee blade	96.0085.00
Case batteries Li Fe PO4 24V 10 Ah (**)	22.0508.00
Case batteries Li Fe PO4 24V 20 Ah (***)	22.0508.01
24V 5A charger	18.0056.00

Driving speed	Km/h	4
Hill climbing ability	%	2
VACUUM		
Motor rating	W	150
Vacuum	mbar/mmH20	48/490
Airflow rating	I/s	30
Noise level	dB(A)	58 / 54 *
TANK		
Type		Double tank
Cleaning solution tank	1	11
Recovery tank	I	12
Weight (empty/with batteries)	Kg	24/27,5
Power supply cable	m	
Dimensions	mm	640x450x502

OF FIGURE ACCEPTAGE		
TYPE	REF. NO.	
Soft cylindrical polypropylene brush	40.5000.01	
Hard cylindrical polypropylene brush	40.5000.02	
Tynex cylindrical brush grit 360	40.5000.03	
Tynex cylindrical brush grit 80	40.5000.08	
Microfiber cylindrical brush	40.5000.04	
Car charger 24-12V 3A	18.0065.00	
Kit case power supply 230V	22.0509.00	

- (*) Silent mode function
- (**) For 10 Ah version
- (***) For 20 Ah version

RAPID 15 E 38

COMPACT WALK BEHIND SCRUBBER DRYERS RAPID 15 SERIES

The small walk behind scrubber dryer Rapid 15, has been further improved in its structural features and functionalities. A complete set of combined and synergical solutions makes Rapid 15 the most suitable solution for any cleaning task in small-medium areas. Rapid 15 distinctive feature is flexibility. The front knob allows the user to adjust the brush incidence to the floor, so ensuring a perfect adherence to any working surface with excellent cleaning results. The squeegee system perfectly covers the water track in any condition, for excellent drying results. And the new pedal lifting system makes it today even more comfortable for the user and reliable. Innovative features that, together with the compact dimensions, make Rapid 15 the perfect solution for every environment and surface, above all in narrow spaces. Rapid 15 E is the electric version, with a standard 15 meters cable.





rotation







Squeegee and Removable lid +

New squeegee Adjustable handle floating ball + filter lifting system with pedal

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 15 E 38	10.0060.01	1

TECHNICAL DATA

I LUIINIUAL DAIA		
FEATURES		
Cleaning width	mm	385
Squeegee width	mm	450
Productivity (theor./practical)	m²/h	1.540 - 770
Power supply		Cable 230V - 50 Hz
Installed power	W	620
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	385 - 15" x 1
Motor rating x No	Wxnr	370 x 1
Motor speed	rpm	150
Down pressure - Contact pressure	Kg - g /cm ²	21 - 26,7
TRACTION		
Motor rating	W	

Km/h	
%	2
W	250
mbar/mmH20	68 / 700
I/s	28
dB(A)	65
	Double tank
1	15
1	16
Kg	40
m	15
mm	855x430x1100
	W mbar/mmH20 I/s dB(A)

STANDARD ACCESSORIES

ТҮРЕ	REF. NO.
15" Polipropylene brush ø 0.7	40.0008.00
Filling hose	30.0024.00
Front Polyurethane blade	39.0070.00
Rear Polyurethane blade	39.0071.00
15 m detachable cable	34.0285.00

OI HONAL AUGEOCOTILE	
TYPE	REF. NO.
15" Polipropylene brush soft ø 0.5	40.0408.00
15" Polipropylene brush ø 0.9	40.0108.00
15" tynex brush grit 240 - ø 0.9	40.0208.00
Pad Holder 335 mm (for 15" pad)	40.1008.00
Front rubber blade	39.0077.00
Rear rubber blade	39.0078.00
Splashquard with bristles	95.0088.00

RAPID 15 M 38 BC/HYBRI



COMPACT WALK BEHIND SCRUBBER DRYERS RAPID 15 SERIES

Rapid 15 represents an important point of reference in the segment of compact scrubber dryers. Its modern design is able to guarantee personality, ergonomics and, most of all, compact dimensions to clean where other scrubber dryers cannot arrive or have difficulty. A functional aesthetics encompasses a top-notch technical solutions system: - Hybrid: the innovative system (only available in the Hybrid RAPID 15 version) which combines power supply with battery power in order to guarantee the perfect mix between performance, working time and prolonged cleaning sessions; - The front knob over the brush head allows to adjust its angle of incidence, enabling RAPID 15 to perfectly adhere to the working surface in any situation and with any kind of accessories to give excellent results; - The practical external wheel allows to adjust the height of the head, avoiding overloads of the engine on "difficult" surfaces. In this way RAPID 15 is able to work everywhere without any problems. - The suction motor guarantees an excellent drying performance and today it is even more reliable thanks to a new protection filter; - The squeegee, which is able to turn up to 270°, is today even more practical thanks to its innovative pedal lift system, which allows to safely and practically lift it in any situation Maximum functionality and performance which, together with its reduced dimensions and its long working time (unlimited in the hybrid version) make RAPID 15 the optimal solution for any kind of environment and surfaces, even the narrowest and least accessible ones.















External wheel adjustable pressure

Squeegee and rotation

Kit Hybrid

New squeegee pedal

Removable lid + Adjustable handle lifting system with floating ball + filter

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 15 M 38 BC	13.0050.01	1
RAPID 15 Hybrid	14.0050.01	1

TECHNICAL DATA

TECHNICAL DATA		
FEATURES		
Cleaning width	mm	385
Squeegee width	mm	450
Productivity (theor./practical)	m²/h	1.540 - 920
Power supply	Battery 24V (BC Cable 230 V - 5	version) / Battery 24V + 60 Hz (for Hybrid version)
Installed power	W	510
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	385 - 15" x 1
Motor rating x No	Wxnr	260 x 1
Motor speed	rpm	130
Down pressure - Contact pressure	Kg - g /cm ²	25,5 - 32,4
TRACTION		
Motor rating	W	

STANDARD ACCESSORIES

TYPE	REF. NO.
15" Polipropylene brush ø 0.7	40.0008.00
Filling hose	30.0024.00
Front Polyurethane blade	39.0070.00
Rear Polyurethane blade	39.0071.00
On board battery charger 24V 5A (Schuko plug 220-240V) (*)	18.0032.00
Batteries set (2 pcs) 12V 25Ah (*)	18.0017.01

Driving speed	Km/h	
Hill climbing ability	%	2
VACUUM		
Motor rating	W	250
Vacuum	mbar/mmH20	68 / 700
Airflow rating	I/s	28
Noise level	dB(A)	65
TANK		
Туре		Double tank
Cleaning solution tank	I	15
Recovery tank	I	16
Weight (empty/with batteries)	Kg	40/62,2 (BC) - 40/49,5 (Hybrid)
Power supply cable	m	15 (for Hybrid version)
Dimensions	mm	865x430x1100

OI HOMAL ACCEDEDINES	
ТҮРЕ	REF. NO.
15" Polipropylene brush soft ø 0.5	40.0408.00
15" Polipropylene brush ø 0.9	40.0108.00
15" tynex brush grit 240 - ø 0.9	40.0208.00
Pad Holder 335 mm (for 15" pad)	40.1008.00
Front rubber blade	39.0077.00
Rear rubber blade	39.0078.00
Splashquard with bristles	95.0088.00

RAPID 30 SM 45



WALK BEHIND SCRUBBER DRYERS RAPID 30 SERIES - MANUAL

RAPID 30 SM 45 TOUCH is the new born in the RAPID family. The new design, makes the machine a masterpiece of aesthetic and ergonomics. Then 30 liters of tank capacity, an high manoeuvrability and above all a complete set of integrated solutions making RAPID 30 suitable for any environment and surface: - Thanks to the new sensor TOUCH SYSTEM. RAPID 30 TOUCH can be moved and controlled only using a thumb: intuitive, user friendly and reliable. - Compact squeegee: large only 65 cm, and adjustable, for excellent drying results. - A complete set of filters to protect the main components and give to RAPID 30 the max reliability. - Performance: high productivity, remarkable running time (around 2 h), top cleaning results. RAPID 30 SM 45 TOUCH is available in three versions: basic, with standard on board charger and full package (standard on board charger + batteries).















Control panel

tank filter

"Built in" solution Adjustable and

Debris tray + compact squeegee recovery tank filter tank

Tiltable recovery

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 30 SM 45 TOUCH	10.0187.01	1
RAPID 30 SM 45 BC TOUCH	13.0187.01	1

TECHNICAL DATA

I EUIIIIIUAE DAIA		
FEATURES		
Cleaning width	mm	430
Squeegee width	mm	650
Productivity (theor./practical)	m²/h	1720 - 1030
Power supply		Battery 24V
Installed power	W	600
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	430 - 17" x 1
Motor rating x No	Wxnr	200 x 1
Motor speed	rpm	120
Down pressure - Contact pressure	Kg - g /cm ²	18 - 17,4
TRACTION		
Motor rating	W	

Driving speed	Km/h	4
Hill climbing ability	%	2
VACUUM		
Motor rating	W	400
Vacuum	mbar/mmH20	1189
Airflow rating	I/s	28
Noise level	dB(A)	64
TANK		
Type		Double tank
Cleaning solution tank	1	30
Recovery tank	1	33
Weight (empty/with batteries)	Kg	66 / 104
Dimensions	mm	1210x560x1020

STANDARD ACCESSORIES

ТҮРЕ	REF. NO.
Solution tank filling hose	30.0024.00
17" Polypropylene brush ø 0.7	40.0002.00
On board charger 24 V 5 A (*)	22.0531.00
Gel batteries set (2 pcs) 12 V 50 Ah (*)	18.0026.00
Front + rear rubber blades	96.0010.00

(*) For BC version

ТҮРЕ	REF. NO.
17" Polypropylene brush ø 0.9	40.0102.00
17" Tynex brush ø 1.2 grit 80	40.0202.00
Pad holder 420 mm (for 17" pad)	40.1007.00
Set front + rear polyurethane squeegee blades	96.0011.00

RAPID 40 E 55



WALK BEHIND SCRUBBER DRYERS RAPID 40 - ELECTRIC

Rapid 40 E 55 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment and the double brush pressure make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. RAPID 40 E 55 TOUCH is available with a brand new and remarkable addition: TOUCH SYSTEM, the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 E 55 TOUCH with a finger has never been so practical and intuitive! 40-litre tank capacity and a standard 25-meter cable included.















Touch System

"Built in" solution tank filter

Adjustable squeegee

Compact squeegee

Debris tray + vacuum filter

Tiltable recovery tank

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 40 E 55 TOUCH	10.0294.01	1

TECHNICAL DATA

FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theor./practical)	m²/h	2120 - 1060
Power supply		Cable 230V - 50 Hz
Installed power	W	1360
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x r	ır 530 - 21" x 1
Motor rating x No	W x nr	750 x 1
Motor speed	rpm	170
Down pressure - Contact pressure	Kg - g /cm ²	29 - 18,8 ; 34 - 22
TRACTION		
Motor rating	W	

Driving speed	Km/h	4
Hill climbing ability	%	2
VACUUM		
Motor rating	W	600
Vacuum	mbar/mmH20	1250
Airflow rating	I/s	30
Noise level	dB(A)	63
TANK		
Туре		Double tank
Cleaning solution tank	I	40
Recovery tank	I	42
Weight (empty/with batteries)	Kg	91,5
Power supply cable	m	25
Dimensions	mm	1210x560x1040

STANDARD ACCESSORIES

ТҮРЕ	REF. NO.
Solution tank filling hose	30.0024.00
25 m detachable cable	34.0427.00
21" Polypropylene brush ø 0.7	40.0003.00
Detachable brush deck splash guard (without bristles)	24.0265.00
Brush deck plash guard's bristles	40.4003.00
Set front+rear rubber squeegee blades	95.0091.00

TYPE	REF. NO.
21" Polipropylene brush ø 0.9	40.0103.00
21" Polypropylene brush ø 1.2	40.0303.00
21" Tynex brush ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.00
Set front + rear polyurethane squeegee blades	96.0055.00

RAPID 40 SM 55



WALK BEHIND SCRUBBER DRYERS RAPID 40 - MANUAL

Rapid 40 SM 55 TOUCH is the scrubber dryer which has been specifically conceived for daily use. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Cutting edge features and technical equipment make RAPID 40 SM an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The SM version introduces itself with top-notch innovations. • Simply Manual: a solutions system which is able to combine the best scrubbing and drying performance with an extreme ease of use: the result is a perfect mix between practicality and cost-effectiveness which guarantees the best operational performance. • TOUCH SYSTEM: the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 with a finger has never been so practical and intuitive! RAPID 40 SM 55 TOUCH is available in two versions: a basic one and a full-package one which includes batteries and a battery charger.















Control panel

Touch System

"Built in" solution Debris tray + tank filter

vacuum filter

Adjustable and compact squeegee

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 40 SM 55 TOUCH	10.0231.01	1
RAPID 40 SM 55 BC TOUCH	13.0231.01	1

TECHNICAL DATA

FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theor./practical)	m²/h	2120 - 1270
Power supply		Battery 24V
Installed power	W	750
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	530 - 21" x 1
Motor rating x No	Wxnr	350 x 1
Motor speed	rpm	115
Down pressure - Contact pressure	Kg - g /cm ²	25,5 - 16,5
TRACTION		
Motor rating	W	

Driving speed	Km/h	4
Hill climbing ability	%	2
VACUUM		
Motor rating	W	400
Vacuum	mbar/mmH20	1189
Airflow rating	I/s	28
Noise level	dB(A)	63
TANK		
Type		Double tank
Cleaning solution tank	1	40
Recovery tank		42
Weight (empty/with batteries)	Kg	90,5 / 143,5
Dimensions	mm	1210x560x1040

STANDARD ACCESSORIES

ТҮРЕ	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
On board charger 24 V 5 A (*)	22.0531.00
Gel batteries set (2 pcs) 12 V 50 A (*)	18.0026.00
Front rubber blade	39.0181.00
Rear rubber blade	39.0111.00

OPTIONAL ACCESSORIES

TYPE	REF. NO.
21" Polypropylene brush ø 0.9	40.0103.00
21" Polypropylene brush ø 1.2	40.0303.00
21" Tynex brush ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.00
Set front + rear polyurethane squeegee blades	96.0055.00

(*) For BC version

RAPID 40 M 55



WALK BEHIND SCRUBBER DRYERS RAPID 40 - MANUAL

Rapid 40 M 55 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment - 40-litre tank capacity, interactive control panel, double brush pressure, "silent mode" function, the new chemical mixing system- make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. RAPID 40 is available with a brand new and remarkable addition: TOUCH SYSTEM, the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 M 55 TOUCH with a finger has never been so practical and intuitive!



















Control panel

Password for reliability and ease of use

Touch System

"Built in" solution Adjustable tank filter

squeegee

Compact squeegee

Debris trav + vacuum filter

Tiltable recovery tank

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 40 M 55 TOUCH	10.0291.01	1
RAPID 40 M 55 BC CHEM TOUCH	17.0291.01	1

TECHNICAL DATA

TECHNICAL DATA		
FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theor./practical)	m²/h	2120 - 1270
Power supply		Battery 24V
Installed power	W	1060
Advancement		Manual
BRUSHES		
Diameter - Pad x No	mm - inch x nr	530 - 21" x 1
Motor rating x No	W x nr	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g /cm ²	25,5 - 16,5 ; 30,5 - 19,7
TRACTION		
Motor rating	W	

Driving speed	Km/h	4
Hill climbing ability	%	2
VACUUM		
Motor rating	W	550
Vacuum	mbar/mmH20	1250
Airflow rating	I/s	30
Noise level	dB(A)	63/57*
TANK		
Type		Double tank
Cleaning solution tank	1	40
Recovery tank	1	42
Weight (empty/with batteries)	Kg	90,5
Dimensions	mm	1210x560x1040

STANDARD ACCESSORIES

ТҮРЕ	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
On board charger 24 V 9 A (**)	22.0519.00
Battery set (2 pcs) 12 V 76 Ah (**)	18.0000.00
Detachable brush deck splash guard (without bristles)	24.0265.00
Brush deck plash guard's bristles	40.4003.00
Set front+rear rubber squeegee blades	95.0091.00
Chemical mixing system (**)	96.0048.00

TYPE	REF. NO.
21" Polipropylene brush ø 0.9	40.0103.00
21" Polypropylene brush ø 1.2	40.0303.00
21" Tynex brush ø 1.2 grit 80	40.0203.00
Pad holder 485 mm (for 20" pad)	40.1003.00
Set front + rear polyurethane squeegee blades	96.0055.00

^(*) Silent mode function

^(**) for BC CHEM version

RAPID 40 SD 55



WALK BEHIND SCRUBBER DRYERS RAPID 40 - WITH TRACTION

Rapid 40 SD 55 TOUCH is the scrubber dryer which has been specifically conceived for daily use. The innovative and functional design quarantees the right ergonomics and comfort in the daily activities. Cutting edge features and technical equipment make RAPID 40 SD an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The SD version introduces itself with top-notch innovations. • Simply Driven: a solutions system which is able to combine the best scrubbing and drying performance with an extreme driveability and ease of use: the result is a perfect mix between practicality and cost-effectiveness which quarantees the best operational performance. • TOUCH SYSTEM: the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 with a finger has never been so practical and intuitive! RAPID 40 SD 55 TOUCH is available in two versions: a basic one and a full-package one which includes batteries and a battery charger.













Hill climbing ability



Control panel

Touch System

"Built in" solution tank filter

Debris tray + vacuum filter

Adjustable and compact squeegee

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 40 SD 55 TOUCH	10.0232.01	1
RAPID 40 SD 55 BC TOUCH	13.0232.01	1

TECHNICAL DATA

FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theor./practical)	m²/h	2650 - 1590
Power supply		Battery 24V
Installed power	W	1090
Advancement		with traction
BRUSHES		
Diameter - Pad x No	mm - inch x nr	530 - 21" x 1
Motor rating x No	Wxnr	350 x 1
Motor speed	rpm	115
Down pressure - Contact pressure	Kg - g /cm ²	25,5 - 16,5
TRACTION		
Motor rating	W	180

VACCOUNT		
Motor rating	W	550
Vacuum	mbar/mmH20	1791
Airflow rating	I/s	30
Noise level	dB(A)	63
TANK		
Туре		Double tank
Cleaning solution tank	1	40
D 1 1		40
Recovery tank		42
Weight (empty/with batteries)	Kg	109 / 189
,	Kg mm	·=

STANDARD ACCESSORIES

ТҮРЕ	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
On board charger 24 V 9 A (*)	22.0519.00
Battery set (2 pcs) 12 V 76 Ah (*)	18.0000.00
Front rubber blade	39.0181.00
Rear rubber blade	39.0111.00

OPTIONAL ACCESSORIES

).
3.00
3.00
3.00
3.00
5.00
3.00

(*) For BC version

RAPID 40 D 55



WALK BEHIND SCRUBBER DRYERS RAPID 40 - WITH TRACTION

Rapid 40 D 55 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment - 40-litre tank capacity, three-hour running time, interactive control panel, double brush pressure, "silent mode" function, the new chemical mixing system - make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The wide cleaning path (21" single brush) and the adjustable speed (up to 5 km/h) allow a productivity of up to 2650 m²/h. RAPID 40 is available with a brand new and remarkable addition: TOUCH SYSTEM, the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 with a finger has never been so practical and intuitive!













Driving speed

Hill climbing ability



Control panel

Password for reliability and ease of use

Touch System

"Built in" solution tank filter

Adjustable squeegee

Compact squeegee

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 40 D 55 TOUCH	10.0292.01	1
RAPID 40 D 55 BC CHEM TOUCH	17.0292.01	1

TECHNICAL DATA

FEATURES		
Cleaning width	mm	530
Squeegee width	mm	750
Productivity (theor./practical)	m²/h	2650 - 1590
Power supply		Battery 24V
Installed power	W	1240
Advancement		With traction
BRUSHES		
Diameter - Pad x No	mm - inch x nr	530 - 21" x 1
Motor rating x No	W x nr	500 x 1
Motor speed	rpm	165
Down pressure - Contact pressure	Kg - g /cm ²	25,5 - 16,5 ; 30,5 - 19,7
TRACTION		
Motor rating	W	180

Till Cliffbirly ability	/0	4
VACUUM		
Motor rating	W	550
Vacuum	mbar/mmH20	1250
Airflow rating	I/s	30
Noise level	dB(A)	63/57*
TANK		
Туре		Double tank
Cleaning solution tank	I	40
Recovery tank	I	42
Weight (empty/with batteries)	Kg	109
Dimensions	mm	1210x560x1040

Km/h

5

STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
21" Polypropylene brush ø 0.7	40.0003.00
On board charger 24 V 9 A (**)	22.0519.00
Battery set (2 pcs) 12 V 105 Ah (**)	18.0001.00
Detachable brush deck splash guard (without bristles)	24.0265.00
Brush deck plash guard's bristles	40.4003.00
Set front+rear rubber squeegee blades	95.0091.00
Chemical mixing system (**)	96.0048.00

REF. NO.
40.0103.00
40.0303.00
40.0203.00
40.1003.00
96.0055.00

- (*) Silent mode function
- (**) for BC CHEM version

RAPID 40 D 60



WALK BEHIND SCRUBBER DRYERS RAPID 40 - WITH TRACTION

Rapid 40 D 60 TOUCH is the scrubber dryer which has been specially conceived to meet the most specific needs of the cleaning professionals. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. Its features combined with its cutting-edge technical equipment - 40-litre tank capacity, three-hour running time, interactive control panel, double brush pressure, "silent mode" function, the new chemical mixing system make RAPID 40 an important point of reference in its sector, allowing the machine to be the ideal solution for effective cleaning results in every kind of floor and environment. The wide cleaning path (2 x 12" brushes) and the adjustable speed (up to 5 km/h) allow a productivity of up to 3050 m²/h. RAPID 40 is available with a brand new and remarkable addition: TOUCH SYSTEM, the patented touch system which allows the operator to benefit from maximum flexibility and control while using the machine. Simplicity, immediacy and reliability: moving RAPID 40 with a finger has never been so practical and intuitive!



















Control panel

Password for reliability and ease of use

Touch System

tank filter

"Built in" solution Adjustable and compact squeegee

Debris trav + vacuum filter

Chemical mixing system

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
RAPID 40 D 60 TOUCH	10.0293.01	1
RAPID 40 D 60 BC CHEM TOUCH	17.0293.01	1

TECHNICAL DATA

I E O I I I I I I I I I I I I I I I I I		
FEATURES		
Cleaning width	mm	600
Squeegee width	mm	750
Productivity (theor./practical)	m²/h	3050 - 1830
Power supply		Battery 24V
Installed power	W	1190
Advancement		With traction
BRUSHES		
Diameter - Pad x No	mm - inch x nr	310 - 12" x 2
Motor rating x No	Wxnr	450 x 1
Motor speed	rpm	200
Down pressure - Contact pressure	Kg - g /cm ²	27 - 27 ; 32 - 32
TRACTION		
Motor rating	W	180

STANDARD ACCESSORIES

TYPE	REF. NO.
Solution tank filling hose	30.0024.00
12" Polypropylene brush ø 0.7 (**)	40.0001.00
On board charger 24 V 9 A (***)	22.0519.00
Battery set (2 pcs) 12 V 105 Ah (***)	18.0001.00
Detachable brush deck splash guard (without bristles)	24.0266.00
Brush deck plash guard's bristles	40.4007.00
Set front+rear rubber squeegee blades	95.0091.00
Chemical mixing system (***)	96.0048.00

Km/h	5
%	2
W	550
mbar/mmH20	1250
I/s	30
dB(A)	63/57*
	Double tank
1	40
1	42
Kg	116
mm	1125x670x1040
	W mbar/mmH20 I/s dB(A)

REF. NO.
40.0101.00
40.0301.00
40.0201.00
40.1001.00
96.0055.00

^(*) Silent mode function

^{(**) 2} Brushes on standard equipment

^(***) for BC CHEM version

SW2 700 D

WALK BEHIND SCRUBBER DRYERS S2 SERIES - WITH TRACTION

SW2 700 D due to the double traction with adjustable speed control is an easy-to-operate scrubber drier with excellent manoeuvrability and operating safety assured under any working condition. The BC version is equipped with on-board battery charger and 4 gel batteries. A solid, powerful and reliable machine with a very ergonomic design. Adjustable handle. Intuitive control panel with on-board diagnostic, battery hour counter and potentiometer to adjust working speed. The brush head comes as a standard with two powerful gear motors, bumper wheels and splashguard. Easy access for maintenance and











Recovery tank with gas spring

Adjustable squeegee

Control panel

Strong frame

PRODUCT IDENTIFICATION

TYPE	REF. NO.	PIECES/PALLET
SW2 700 D	10.0270.01	1
SW2 700 D BC	13.0270.01	1

TECHNICAL DATA

mm	700
mm	950
m²/h	3400 - 2040
	Battery 24V
W	1520
	With traction
mm - inch x nr	360 - 14" x 2
Wxnr	350 x 2
rpm	190
Kg - g /cm ²	35 - 31,2
W	250
	mm m²/h W mm - inch x nr W x nr rpm Kg - g /cm²

_				_	_		_	_		
CI	ГΛΙ	чп	ΛГ	חו	Л	rr	, E	uu	nn	IES
-	ш		/A		ш			•	I I I	

ТҮРЕ	REF. NO.
14" Polipropylene brush Ø 0,9 (*)	40.0106.00
Brush splashguard	39.0023.00
Front rubber blade	39.0003.00
Rear rubber blade	39.0035.00
Battery set (4 pcs) Gel 6V 180Ah (**)	18.0009.00
On board battery charger 24 V 20 A (**)	22.0046.00

Driving speed	Km/h	5
Hill climbing ability	%	2
VACUUM		
Motor rating	W	550
Vacuum	mbar/mmH20	165 / 1.700
Airflow rating	I/s	32
Noise level	dB(A)	66
TANK		
Туре		Double tank
Cleaning solution tank	1	80
Recovery tank	1	90
Weight (empty/with batteries)	Kg	129 / 255
Dimensions	mm	1250x710x1080

OI HOMAL ACCESSORIES			
ТҮРЕ	REF. NO.		
14" Polypropylene brush Ø 0,7	40.0006.00		
14" Polypropylene brush Ø 1,2	40.0306.00		
14" Tynex brush Grit 80 Ø 0,9	40.0206.00		
Pad holder 345 mm (for 14" pad)	40.1006.00		
Front polyurethane blade	39.0036.00		
Rear polyurethane blade	39.0041.00		

- (*) 2 Brushes on standard equipment
- (**) for BC version